

C 091 D Characteristics

General Characteristics	Standard	Characteristics										
Number of contacts		3	4	5	5 Stereo	6	7	7	8	12	14	
View on termination side of male contact insert												
Contact arrangement	DIN EN 61076-2-106	03-a ✓	04-a ✓	05-a ✓	05-b ✓	06-a ✓	07-a ✓	07-b ✓	08-a ✓	12-a ✓	14-a ✓	
Contact arrangement	IEC 60130-9 ¹⁾	✓	✓		✓	✓		✓	✓			
Electrical Characteristics												
Rated voltage ²⁾	IEC 60664-1	300 V ≈ (100 V ≈)		300 V ≈ (63 V ≈)		100 V ≈ (32 V ≈)		300 V ≈ (63 V ≈)		100 V ≈ (32 V ≈)		150 V ≈ (32 V ≈)
Rated voltage	UL 1977	250 V									60 V	
Rated impulse withstand voltage ²⁾	IEC 60664-1	1500 V (840 V)			1200 V (500 V)		1500 V (840 V)		1200 V (500 V)			
Pollution degree ²⁾	IEC 60664-1	1 (3 ³⁾)										
Installation category	IEC 60664-1	I										
Insulation group	IEC 60664-1	II, 400 ≤ CTI < 600										
Current rating	IEC 60512-5-2 UL 1977	5 A / + 40 °C / + 104 °F please refer also to current derating curves page 59									3 A / + 40 °C / + 104 °F	
Insulation resistance	IEC 60512-3-1	> 10 ¹⁰ Ω ⁴⁾										
Contact resistance	IEC 60512-2-1	< 5 m Ω										
Climatic Characteristics												
Climatic category	IEC 60668-1	40 / 100 / 56										
Temperature range	IEC 60668-1	- 40 °C ... + 100 °C / - 40 °F ... + 212 °F										
Salt Spray Resistance	DIN IEC 60068-2-11, Test Ka	720h										
Mechanical Characteristics												
IP-degree	IEC 60529	IP 67 and IP 65 (in mated condition)										
Insertion and withdrawal forces	IEC 60512-13-2	25 N 90.oz	30 N 110.oz	35 N 125.oz		50 N 180.oz		55 N 200.oz		60 N 220.oz	50 N 180.oz	
Mechanical operation	IEC 60512-9-1	Silver ≥ 500 mating cycles Gold ≥ 1000 mating cycles										
Materials												
Housing material		coupling ring brass, strain relief, die cast, nickel plated										
Dielectric material		thermoplastic										
Contact plating		silver plated / gold plated ⁵⁾										
Further Characteristics												
Termination technique		solder, crimp										
Wire gauge		solder: ≤ 0,5 mm ² / 20 AWG crimp: 2 - 6 pol (excluding 5S): 0,09 - 1,00 mm ² / 28 - 18 AWG crimp: 5S, 7, 7S and 8-pol.: 0,09 - 0,75 mm ² / 28 - 20 AWG									solder: ≤ 0,25 mm ² / 24 AWG crimp: 0,09-0,25 mm ² / 28 - 24 AWG	
Flammability		UL 94 V0										
Locking system	IEC 60130-9 DIN EN 61076-2-106	metal screw coupling; tightening torque 0,7 Nm										
UL	UL 1977	Conditions of acceptability										

Caution: Do not connect or disconnect under load. Metal housing parts shall be securely incorporated to protected ground.

¹⁾ Edition 2000-05

²⁾ values in brackets are according to DIN EN 61076-2-106

³⁾ designed acc. pollution degree 2; can be used under pollution degree 3 when the rules of IEC 60644-1 are fulfilled

⁴⁾ under operating conditions >10⁸ Ω

⁵⁾ Remark for gold plated contacts: In order to avoid brittle inter-metallic connections, gold-plated terminals have to be tin-plated in the solder area.

IEC 60 664 ≙ DIN VDE 0110 ; IEC 60 512-x ≙ DIN EN 60 512-x; IEC 60 130-9 ≙ DIN EN 60 130-9; IEC 61076-2-106 ≙ DIN EN 61076-2-106

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

[C091-00V000-120-2](#) [C091-31H006-101-2](#) [C091-31H012-201-2](#) [C091-31S006-800-2](#) [C091-31S008-100-2](#) [C091-61G004-110-2](#) [C091-61G008-110-2](#) [C091-61G012-210-2](#) [C091-61G014-210-2](#) [C091-61N006-120-2](#) [C091-61N008-120-2](#) [T3277-500](#) [T3324-991](#) [T3359-150](#) [T3203-100](#) [T3362-100](#) [C091-31H014-100-2](#) [T3424-551](#) [C091-61G014-110-2](#) [C091-61N003-130-2](#) [T3504-013](#) [T3505-013](#) [T3400-028](#) [T3504-552](#) [T13360609](#) [C091-11D006-001-2](#) [C091-11F006-001-2](#) [C091-11K006-001-2](#) [T3260-013](#) [T3303-550](#) [T3360-130](#) [T3361-130](#) [T3400-551](#) [T3403-300](#) [T3476-018](#) [T3505-002](#) [T3507-150](#) [T3507-900](#) [T3638-404](#) [T 3203 009](#) [T 3262 009](#) [T 3263 009](#) [T 3302 009](#) [T 3303 009](#) [T 3359 009](#) [T 3362 009](#) [T 3363 009](#) [T 3402 009](#) [T 3403 009](#) [T 3477 009](#) [T 3478 009](#) [T 3487 009](#) [T 3506 009](#) [T 3637 009](#) [T 3638 009](#) [T 3652 009](#) [T 3653 009](#) [ZN01 015 0046 1](#) [ZN01 015 0046 2](#) [T3487-400](#) [T3653-404](#) [T3363-420](#) [T3507-420](#) [T3361-004](#) [VN02 015 0047 1](#) [C091-31D012-201-2](#) [C091-31D107-101-2](#) [T3447-100](#) [T3200-002](#) [T3200-004](#) [T3200-013](#) [T3200-028](#) [T3201-002](#) [T3201-005](#) [T3201-013](#) [T3201-028](#) [T3202-000](#) [T3202-009](#) [T3202-100](#) [T3203-109](#) [T3203-400](#) [T3260-004](#) [T3260-028](#) [T3260-048](#) [T3260-551](#) [T3260-552](#) [T3261-002](#) [T3261-004](#) [T3261-005](#) [T3261-013](#) [T3261-018](#) [T3261-028](#) [T3261-048](#) [T3261-055](#) [T3261-551](#) [T3261-552](#) [T3262-018](#) [T3262-100](#) [T3262-300](#) [T3262-400](#)