







FV35

**Pillar Terminal Block
(12 poles)**



TECHNICAL DATA

	IEC Standards	American Standards
Ratings	450V - 24A	300V - 6A
Wire size	2.5 sqmm	20 ÷ 18 AWG
Working Temperature	- 5 ÷ 150°C (short time 180°C)	23 ÷ 239°F
Plastic Material	Polyamide PA6.6 glass filled brown colour, UL94 V0, GWT 960°C	
Metal Parts	Cage insert made in nickel plated brass; M3 Captive screw made in zinc plated steel	
Accessories		

Approvals	File Nr.	Ratings (sqmm/AWG - V - A - T)	Standard References
	E 2678	2.5 sqmm - 450V - 24A - 150°C	EN 60998-1; EN 60998-2-1
	121212	2.5 sqmm - 450V - 24A - 150°C	DIN EN 60998-1; DIN EN 60998-2-1 (VDE 0613)
	E 76048 vol. 1 sec. 1	20 ÷ 18AWG - 300V - 6A - 115 °C	UL 1059; CSA C22-2 N.158-1987
	LR 40455	20 ÷ 14AWG - 300V - 6A	CSA C22-2 N.158-1987; E.C.N 584B

PACKAGING

Type	P-N	Pack.	Dim. Pack. (LxHxP)	Weight (Kg)
FV 35/12P	100612	1000	40x20x40	21.0

DIMENSIONAL
DRAWING

