



KLS7-SMS-102-C3 ON-ON 3P
 KLS7-SMS-103-C3 ON-OFF-ON 3P

KLS7-SMS-202-C3 ON-ON 6P
 KLS7-SMS-203-C3 ON-OFF-ON 6P

Sub-miniature Toggle switch SPECIFICATIONS

Rating: 3A 125VAC; 1.5A 250VAC
 Contact Resistance: 20MΩ max
 Insulation Resistance: 500V DC 1000MΩ Min
 Dielectric Strength: 1000V AC 1 Minute
 Operating Temperature: -25°C +65°C
 Electrical Life :20,000 cycles

Part No.	Description
KLS7-SMS-102-C3	Sub-miniature Toggle switch,3A 125VAC/1.5A 250VAC,Single pole,SPDT ON-ON,Standard Round Handle Length 5.4mm,Right angle PCB terminal 3P.
KLS7-SMS-103-C3	Sub-miniature Toggle switch,3A 125VAC/1.5A 250VAC,Single pole,SPDT ON-OFF-ON,Standard Round Handle Length 5.4mm,Right angle PCB terminal 3P.
KLS7-SMS-202-C3	Sub-miniature Toggle switch,3A 125VAC/1.5A 250VAC,Double pole,DPDT ON-ON,Standard Round Handle Length 5.4mm,Right angle PCB terminal 6P.
KLS7-SMS-203-C3	Sub-miniature Toggle switch,3A 125VAC/1.5A 250VAC,Double pole,DPDT ON-OFF-ON,Standard Round Handle Length 5.4mm,Right angle PCB terminal 6P.