

International **IR** Rectifier

PD- 91575B


IRG4PH50KD

INSULATED GATE BIPOLAR TRANSISTOR WITH ULTRAFAST SOFT RECOVERY DIODE

Short Circuit Rated
UltraFast IGBT

Features


- High short circuit rating optimized for motor control, $t_{sc} = 10\mu s$, $V_{CC} = 720V$, $T_J = 125^{\circ}C$, $V_{GE} = 15V$
- Combines low conduction losses with high switching speed
- Tighter parameter distribution and higher efficiency than previous generations
- IGBT co-packaged with HEXFRED™ ultrafast, ultrasoft recovery antiparallel diodes



$V_{CES} = 1200V$
 $V_{CE(on)} \text{ typ.} = 2.77V$
@ $V_{GE} = 15V$, $I_C = 24A$

Benefits

- Latest generation 4 IGBT's offer highest power density motor controls possible
- HEXFRED™ diodes optimized for performance with IGBTs. Minimized recovery characteristics reduce noise, EMI and switching losses
- This part replaces the IRGPH50KD2 and IRGPH50MD2 products
- For hints see design tip 97003



Absolute Maximum Ratings

	Parameter	Max.	Units	
V_{CES}	Collector-to-Emitter Voltage	1200	V	
$I_C @ T_C = 25^{\circ}C$	Continuous Collector Current	45	A	
$I_C @ T_C = 100^{\circ}C$	Continuous Collector Current	24		
I_{CM}	Pulsed Collector Current ①	90		
I_{LM}	Clamped Inductive Load Current ②	90		
$I_F @ T_C = 100^{\circ}C$	Diode Continuous Forward Current	16	W	
I_{FM}	Diode Maximum Forward Current	90		
t_{sc}	Short Circuit Withstand Time	10		
V_{GE}	Gate-to-Emitter Voltage	± 20		
$P_D @ T_C = 25^{\circ}C$	Maximum Power Dissipation	200	$^{\circ}C$	
$P_D @ T_C = 100^{\circ}C$	Maximum Power Dissipation	78		
T_J	Operating Junction and	-55 to +150		
T_{STG}	Storage Temperature Range			
	Soldering Temperature, for 10 sec.	300 (0.063 in. (1.6mm) from case)	g (oz)	
	Mounting Torque, 6-32 or M3 Screw.	10 lbf·in (1.1 N·m)		

Thermal Resistance

	Parameter	Min.	Typ.	Max.	Units
$R_{\theta JC}$	Junction-to-Case - IGBT	—	—	0.64	$^{\circ}C/W$
$R_{\theta JC}$	Junction-to-Case - Diode	—	—	0.83	
$R_{\theta CS}$	Case-to-Sink, flat, greased surface	—	0.24	—	
$R_{\theta JA}$	Junction-to-Ambient, typical socket mount	—	—	40	
Wt	Weight	—	6 (0.21)	—	
1 7/7/2000					

IRG4PH50KD

International
Rectifier

Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
$V_{(\text{BR})\text{CES}}$	Collector-to-Emitter Breakdown Voltage ^③	1200	—	—	V	$V_{\text{GE}} = 0\text{V}$, $I_C = 250\mu\text{A}$
$\Delta V_{(\text{BR})\text{CES}/\Delta T_J}$	Temperature Coeff. of Breakdown Voltage	—	0.91	—	V/ $^\circ\text{C}$	$V_{\text{GE}} = 0\text{V}$, $I_C = 1.0\text{mA}$
$V_{\text{CE}(\text{on})}$	Collector-to-Emitter Saturation Voltage	—	2.77	3.5	V	$I_C = 24\text{A}$ $V_{\text{GE}} = 15\text{V}$
		—	3.28	—		$I_C = 45\text{A}$ See Fig. 2, 5
		—	2.54	—		$I_C = 24\text{A}$, $T_J = 150^\circ\text{C}$
$V_{\text{GE}(\text{th})}$	Gate Threshold Voltage	3.0	—	6.0		$V_{\text{CE}} = V_{\text{GE}}$, $I_C = 250\mu\text{A}$
$\Delta V_{\text{GE}(\text{th})/\Delta T_J}$	Temperature Coeff. of Threshold Voltage	—	-10	—	mV/ $^\circ\text{C}$	$V_{\text{CE}} = V_{\text{GE}}$, $I_C = 250\mu\text{A}$
g_{fe}	Forward Transconductance ^④	13	19	—	S	$V_{\text{CE}} = 100\text{V}$, $I_C = 24\text{A}$
I_{CES}	Zero Gate Voltage Collector Current	—	—	250	μA	$V_{\text{GE}} = 0\text{V}$, $V_{\text{CE}} = 1200\text{V}$
		—	—	6500		$V_{\text{GE}} = 0\text{V}$, $V_{\text{CE}} = 1200\text{V}$, $T_J = 150^\circ\text{C}$
V_{FM}	Diode Forward Voltage Drop	—	2.5	3.5	V	$I_C = 16\text{A}$ See Fig. 13
		—	2.1	3.0		$I_C = 16\text{A}$, $T_J = 150^\circ\text{C}$
I_{GES}	Gate-to-Emitter Leakage Current	—	—	± 100	nA	$V_{\text{GE}} = \pm 20\text{V}$

Switching Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
Q_g	Total Gate Charge (turn-on)	—	180	270	nC	$I_C = 24\text{A}$
Q_{ge}	Gate - Emitter Charge (turn-on)	—	25	38		$V_{\text{CC}} = 400\text{V}$ See Fig.8
Q_{gc}	Gate - Collector Charge (turn-on)	—	70	110		$V_{\text{GE}} = 15\text{V}$
$t_{d(\text{on})}$	Turn-On Delay Time	—	87	—	ns	$T_J = 25^\circ\text{C}$ $I_C = 24\text{A}$, $V_{\text{CC}} = 800\text{V}$ $V_{\text{GE}} = 15\text{V}$, $R_G = 5.0\Omega$ Energy losses include "tail" and diode reverse recovery See Fig. 9,10,18
t_r	Rise Time	—	100	—		
$t_{d(\text{off})}$	Turn-Off Delay Time	—	140	300		
t_f	Fall Time	—	200	300		
E_{on}	Turn-On Switching Loss	—	3.83	—	mJ	See Fig. 10,11,18
E_{off}	Turn-Off Switching Loss	—	1.90	—		
E_{ts}	Total Switching Loss	—	5.73	7.9		
t_{sc}	Short Circuit Withstand Time	10	—	—	μs	$V_{\text{CC}} = 720\text{V}$, $T_J = 125^\circ\text{C}$ $V_{\text{GE}} = 15\text{V}$, $R_G = 5.0\Omega$
$t_{d(\text{on})}$	Turn-On Delay Time	—	67	—	ns	$T_J = 150^\circ\text{C}$, See Fig. 10,11,18 $I_C = 24\text{A}$, $V_{\text{CC}} = 800\text{V}$ $V_{\text{GE}} = 15\text{V}$, $R_G = 5.0\Omega$, Energy losses include "tail" and diode reverse recovery
t_r	Rise Time	—	72	—		
$t_{d(\text{off})}$	Turn-Off Delay Time	—	310	—		
t_f	Fall Time	—	390	—		
E_{ts}	Total Switching Loss	—	8.36	—	mJ	
L_E	Internal Emitter Inductance	—	13	—	nH	Measured 5mm from package
C_{ies}	Input Capacitance	—	2800	—	pF	$V_{\text{GE}} = 0\text{V}$ $V_{\text{CC}} = 30\text{V}$ See Fig. 7 $f = 1.0\text{MHz}$
C_{oes}	Output Capacitance	—	140	—		
C_{res}	Reverse Transfer Capacitance	—	53	—		
t_{rr}	Diode Reverse Recovery Time	—	90	135	ns	$T_J = 25^\circ\text{C}$ See Fig.
		—	164	245		$T_J = 125^\circ\text{C}$ 14
I_{rr}	Diode Peak Reverse Recovery Current	—	5.8	10	A	$T_J = 25^\circ\text{C}$ See Fig.
		—	8.3	15		$T_J = 125^\circ\text{C}$ 15
Q_{rr}	Diode Reverse Recovery Charge	—	260	675	nC	$T_J = 25^\circ\text{C}$ See Fig.
		—	680	1838		$T_J = 125^\circ\text{C}$ 16
$di_{(\text{rec})M/dt}$	Diode Peak Rate of Fall of Recovery During t_b	—	120	—	A/ μs	$T_J = 25^\circ\text{C}$ See Fig.
		—	76	—		$T_J = 125^\circ\text{C}$ 17




Fig. 1 - Typical Load Current vs. Frequency
 (Load Current = I_{RMS} of fundamental)




Fig. 2 - Typical Output Characteristics




Fig. 3 - Typical Transfer Characteristics

IRG4PH50KD

International
IR Rectifier




Fig. 4 - Maximum Collector Current vs. Case Temperature




Fig. 5 - Typical Collector-to-Emitter Voltage vs. Junction Temperature







Fig. 6 - Maximum Effective Transient Thermal Impedance, Junction-to-Case




**Fig. 7 - Typical Capacitance vs.
Collector-to-Emitter Voltage**



**Fig. 8 - Typical Gate Charge vs.
Gate-to-Emitter Voltage**



**Fig. 9 - Typical Switching Losses vs. Gate
Resistance**



**Fig. 10 - Typical Switching Losses vs.
Junction Temperature**

IRG4PH50KD

International
IR Rectifier




Fig. 11 - Typical Switching Losses vs.
Collector Current




Fig. 12 - Turn-Off SOA




Fig. 13 - Typical Forward Voltage Drop vs. Instantaneous Forward Current

International
 Rectifier




Fig. 14 - Typical Reverse Recovery vs. di_f/dt

IRG4PH50KD




Fig. 15 - Typical Recovery Current vs. di_f/dt




Fig. 16 - Typical Stored Charge vs. di_f/dt




Fig. 17 - Typical $di_{(rec)}M/dt$ vs. di_f/dt

IRG4PH50KD

International
IR Rectifier




Fig. 18a - Test Circuit for Measurement of I_{LM} , E_{on} , $E_{off(diode)}$, t_{rr} , Q_{rr} , I_{rr} , $t_{d(on)}$, t_r , $t_{d(off)}$, t_f




Fig. 18b - Test Waveforms for Circuit of Fig. 18a, Defining E_{off} , $t_{d(off)}$, t_f




Fig. 18c - Test Waveforms for Circuit of Fig. 18a, Defining E_{on} , $t_{d(on)}$, t_r




Fig. 18d - Test Waveforms for Circuit of Fig. 18a, Defining E_{rec} , t_{rr} , Q_{rr} , I_{rr}




Figure 18e. Macro Waveforms for Figure 18a's Test Circuit




Figure 19. Clamped Inductive Load Test Circuit




Figure 20. Pulsed Collector Current Test Circuit


IRG4PH50KD

International
IR Rectifier

Notes:

- ① Repetitive rating: $V_{GE}=20V$; pulse width limited by maximum junction temperature (figure 20)
- ② $V_{CC}=80\% (V_{CES})$, $V_{GE}=20V$, $L=10\mu H$, $R_G=5.0\Omega$ (figure 19)
- ③ Pulse width $\leq 80\mu s$; duty factor $\leq 0.1\%$.
- ④ Pulse width $5.0\mu s$, single shot.

Case Outline — TO-247AC



International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
IR EUROPEAN REGIONAL CENTRE: 439/445 Godstone Rd, Whyteleafe, Surrey CR3 OBL, UK Tel: ++ 44 (0)20 8645 8000
IR CANADA: 15 Lincoln Court, Brampton, Ontario L6T3Z2, Tel: (905) 453 2200
IR GERMANY: Saalburgstrasse 157, 61350 Bad Homburg Tel: ++ 49 (0) 6172 96590
IR ITALY: Via Liguria 49, 10071 Borgaro, Torino Tel: ++ 39 011 451 0111
IR JAPAN: K&H Bldg., 2F, 30-4 Nishi-Ikebukuro 3-Chome, Toshima-Ku, Tokyo 171 Tel: 81 (0)3 3983 0086
IR SOUTHEAST ASIA: 1 Kim Seng Promenade, Great World City West Tower, 13-11, Singapore 237994 Tel: ++ 65 (0)888 4630
IR TAIWAN: 16 Fl. Suite D. 207, Sec. 2, Tun Haw South Road, Taipei, 10673 Tel: 886-(0)2 2377 9936
Data and specifications subject to change without notice. 7/00

Note: For the most current drawings please refer to the IR website at:
<http://www.irf.com/package/>